



CARRETE DESMONTAJE PN10/16/25 DOBLE BRIDA

DISMANTLING JOINT PN10/16/25 FLANGED

Fig. 6420

Características / Features

| | |
|------------------------------------|---|
| Bridas / Flanged | PN10/16/25 |
| Presión nominal / Nominal pressure | 10-16-25 bar |
| Test presión / Pressure test | 15/24/37,5 bar |
| Recubrimiento / Coating | Resina epoxi fundida / Fusion epoxi coated |

Materiales / Materials

| Descripción / Part name | Material |
|---|---|
| Viola / Pipe | AISI304/316/316L |
| Bridas / Flanged | Ac. Carbono. Carbon Steel/AISI304/316/316L |
| Junta / Gasket | Nitrilo/EPDM |
| Tornillos brida de apriete / Clamping flange bolts | Acero Dicromatizado/Acero Inox / Dichromatized steel/Stainless steel |

Dimensiones / Main dimensions

| Tamaño / Size | | L | L1 | L2 |
|---------------|-----|-----|-----|-----|
| DN | NPS | | | |
| 50 | 2" | 150 | 180 | 210 |
| 65 | 2½" | 150 | 180 | 210 |
| 80 | 3" | 150 | 180 | 210 |
| 100 | 4" | 150 | 180 | 210 |
| 125 | 5" | 150 | 180 | 210 |
| 150 | 6" | 150 | 180 | 210 |
| 200 | 8" | 160 | 200 | 240 |
| 250 | 10" | 160 | 200 | 240 |
| 300 | 12" | 160 | 200 | 240 |
| 350 | 14" | 200 | 240 | 280 |
| 400 | 16" | 200 | 240 | 280 |
| 450 | 18" | 200 | 240 | 280 |
| 500 | 20" | 200 | 240 | 280 |
| 600 | 24" | 260 | 300 | 340 |
| 700 | 28" | 260 | 300 | 340 |
| 800 | 32" | 260 | 300 | 340 |
| 900 | 36" | 260 | 300 | 340 |
| 1000 | 40" | 260 | 300 | 340 |
| 1100 | 44" | 260 | 300 | 340 |
| 1200 | 48" | 260 | 300 | 340 |

