

FILTRO TEMPORAL CÓNICO PN16/40/150#/300#/600# WAFER DIN/ANSI

CONICAL TEMPORARY STRAINER PN16/40/150#/300#/600# WAFER DIN/ANSI



Fig. 7130

Características / Features

Diseño / Design	Tamiz cónico / Conical screen
Rating	PN16/40/150#/300#/600#
Distancia entre caras / Face to face	Según tabla de dimensiones / According to dimension table
Extremos / Ends	Wafer

Materiales / Materials

Descripción / Part name	Material
Disco / Disc	AISI 304 / AISI 316
Tamiz / Screen	AISI 304 / AISI 316

Dimensiones / Main dimensions

Tamaño / Size		A	B	C (mm)				D
DN	NPS	(mm)	(mm)	PN16/40	150Lb	300Lb	600Lb	(mm)
40	1 1/2"	101,6	31,75	94	79,38	88,9	88,9	101,6
50	2"	114,3	44,45	109	98,43	104,78	104,78	101,6
65	2 1/2"	139,7	57,15	129	117,48	125,83	123,83	101,6
80	3"	165,1	69,85	144	130,18	142,88	142,88	101,6
100	4"	215,9	88,9	170	168,28	174,63	196,85	101,6
125	5"	266,7	117,48	194	190,5	209,55	234,95	127
150	6"	330,2	139,7	224	215,9	244,48	260,35	127
200	8"	431,8	180,98	286	273,05	301,63	314,33	127
250	10"	533,4	228,6	-	333,38	355,6	393,7	152,4
300	12"	635	276,23	-	403,23	415,93	450,85	152,4
350	14"	660,4	320,68	-	444,5	479,43	485,78	152,4
400	16"	749,3	368,3	-	508	533,4	558,8	152,4
450	18"	838,2	415,93	-	542,93	590,55	606,43	152,4
500	20"	939,8	466,73	-	600,08	647,7	676,28	203,2
600	24"	1117,6	568,33	-	711,2	768,35	784,23	203,2

