

PURGADOR TERMODINAMICO CON FILTRO PN40

THERMODYNAMIC STEAM TRAP WITH STRAINER PN40



Fig. 7010

Características / Features

Rating	PN40
Conexión / Connection	Rosca BSP / BSP Threaded
Presión máx. permitida / Max. Allowable pressure	63 bar
Temperatura máx. permitida / Max. Allowable temperature	400 °C
Presión máx. de operación / Max. Operating pressure	40 bar
Temperatura máx. de operación / Max. Operating temperature	350 °C

Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	CA-40 / 1,4028
2	Disco / Disc	AISI 420 / 1,4021
3	Tamiz / Strainer screen	AISI 304 / 1,4301
4	Junta / Gasket	St. St. / Graphite

Dimensiones / Main dimensions

Tamaño / Size	A	B	C	D	E	Peso / Weight Kg
3/8"	70	35	40	73,5	39	0,58
1/2"	70	35	40	73,5	39	0,61
3/4"	75	35	40	77,5	46	0,90
1"	90	35	50	90	52,5	1,30

Tamaño / Size	ΔP (bar)												
	0,5	1	3	6	9	12	15	18	21	24	30	35	40
	Caudal / Flow (Kg/h)												
3/8"	80	85	115	150	190	210	250	300	310	350	420	490	510
1/2"	140	170	250	330	400	490	500	580	605	690	720	800	820
3/4"	190	225	345	480	590	700	750	810	900	990	1100	1300	1390
1"	290	350	500	700	830	995	1200	1290	1320	1500	1750	1800	1995

