



VÁLVULA DE BOLA 2 PIEZAS PN16/40 BRIDAS DIN

BALL VALVE 2 PIECES PN16/40 DIN FLANGED

Fig. 5151

Características / Features

| | |
|---|---|
| Diseño / Design | 2 piezas atornilladas. Paso total / 2 bolted pieces. Full bore |
| Rating | PN16 (2½"-8") - PN40 (½"-2") |
| Distancia entre caras / Face to face | EN558-1 serie 27 (DIN 3202 F18) |
| Extremos / Ends | Bridas DIN / DIN Flanged |

Materiales / Materials

| N° | Descripción / Part name | Material |
|----|-------------------------|--------------------------------|
| 1 | Cuerpo / Body | A216 WCB / ASTM A351 CF8M |
| 2 | Bola / Ball | ASTM A351 CF8 / ASTM A351 CF8M |
| 3 | Eje / Stem | AISI 304 / AISI 316 |
| 4 | Asiento / Seat | PTFE |

Dimensiones / Main dimensions

| Tamaño / Size | | PN | L | D2 | D1 | D | n-ød | H | Peso / Weight Kg |
|---------------|-----|----|-----|-----|-----|-----|-------|-----|---------------------|
| DN | NPS | | | | | | | | |
| 15 | ½" | 40 | 115 | 45 | 65 | 95 | 4x14 | 84 | 2 |
| 20 | ¾" | 40 | 120 | 58 | 75 | 105 | 4x14 | 89 | 3 |
| 25 | 1" | 40 | 125 | 68 | 85 | 115 | 4x14 | 90 | 4 |
| 32 | 1¼" | 40 | 130 | 78 | 100 | 140 | 4x18 | 100 | 6 |
| 40 | 1½" | 40 | 140 | 88 | 110 | 150 | 4x18 | 109 | 9 |
| 50 | 2" | 40 | 150 | 102 | 125 | 165 | 4x18 | 120 | 10 |
| 65 | 2½" | 16 | 170 | 122 | 145 | 185 | 4x18 | 135 | 13 |
| 80 | 3" | 16 | 180 | 138 | 160 | 200 | 8x18 | 153 | 16 |
| 100 | 4" | 16 | 190 | 158 | 180 | 220 | 8x18 | 194 | 24 |
| 125 | 5" | 16 | 325 | 188 | 210 | 250 | 8x18 | 225 | 44 |
| 150 | 6" | 16 | 350 | 212 | 240 | 285 | 8x22 | 275 | 55 |
| 200 | 8" | 16 | 400 | 268 | 295 | 340 | 12x22 | 340 | 93 |

