



Fig. 5203

# VÁLVULA DE COMPUERTA HUSILLO EXTERIOR PN10 BRIDAS DIN

## GATE VALVE OS&Y PN10 DIN FLANGED

### Características / Features

Diseño / Design	DIN 3352. Tapa atornillada. Husillo exterior. Cierre metal-metal / DIN 3352. Bolted bonnet. OS&Y. Metal seated
Rating	PN10
Distancia entre caras / Face to face	DIN 3202-F4
Extremos / Ends	Bridas DIN / DIN Flanged

### Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	GG25
2	Asiento / Seat	Latón/Brass. AISI304L
3	Cuña / Wedge	GG25
4	Eje / Stem	AISI 420
5	Junta / Gasket	Cartón / Cellulose

### Dimensiones / Main dimensions

Tamaño / Size		D1	D2	D	L	H	n-ød	Peso / Weight Kg
DN	NPS							
40	1½"	84	110	150	140	250	4-ø18	13
50	2"	99	125	165	150	342	4-ø18	14
65	2½"	118	145	185	170	397	4-ø18	19
80	3"	132	160	200	180	468	8-ø18	25
100	4"	156	180	220	190	536	8-ø18	32
125	5"	184	210	250	200	640	8-ø18	45
150	6"	211	240	285	210	746	8-ø23	59
200	8"	266	295	340	230	960	8-ø23	88
250	10"	319	350	395	250	1151	12-ø23	138
300	12"	370	400	445	270	1334	12-ø23	178
350	14"	429	460	505	290	1525	16-ø23	240
400	16"	480	515	565	310	1825	16-ø28	420
450	18"	530	565	615	330	2072	20-ø28	485
500	20"	582	620	670	350	2302	20-ø28	650
600	24"	682	725	780	390	2650	20-ø31	920

