



VÁLVULA DE COMPUERTA SERIE F5 PN16 BRIDAS DIN

GATE VALVE F5 SERIES PN16 DIN FLANGED

Fig. 5210

Características / Features

Diseño / Design	DIN 3352. Tapa atornillada. Husillo exterior. Cierre metal-metal / DIN 3352. Bolted bonnet. OS&Y. Metal seated
Rating	PN16
Distancia entre caras / Face to face	DIN 3202-F5
Extremos / Ends	Bridas DIN / DIN Flanged

Materiales / Materials

N°	Descripción / Part name	Material
1	Cuerpo / Body	GG25
2	Asiento / Seat	AISI 304L
3	Cuña / Wedge	GG25
4	Eje / Stem	AISI 420
5	Junta / Gasket	Cartón / Cellulose

Dimensiones / Main dimensions

Tamaño / Size		D1	D2	D	L	H	n-ød	Peso / Weight
DN	NPS							Kg
40	1½"	84	110	150	240	340	4-ø19	15
50	2"	99	125	165	250	354	4-ø19	17
65	2½"	118	145	185	270	390	4-ø19	22
80	3"	132	160	200	280	435	8-ø19	28
100	4"	156	180	220	300	545	8-ø19	36
125	5"	184	210	250	325	625	8-ø19	51
150	6"	211	240	285	350	750	8-ø23	71
200	8"	266	295	340	400	980	12-ø23	83
250	10"	319	355	405	450	1130	12-ø28	147
300	12"	370	410	460	500	1330	12-ø28	210
350	14"	429	470	520	550	1533	16-ø28	280
400	16"	480	525	580	600	1905	16-ø31	487
450	18"	548	585	640	650	2072	20-ø31	563
500	20"	609	650	715	700	2302	20-ø34	754
600	24"	720	770	840	800	2650	20-ø37	1067

